Product sheet

Miniature connector



Product Contacts: 6 DIN, female panel mount


connector, screwed from front, IP 67,


shielded

Pole

Area Article number Push-Pull IP67 Series 440 09 4820 81 06

Illustration





Contact Arrangement

You can find the item description and assembly instruction on the next page.

Technical data

Common values

Connector Design
Connector locking system
Termination
Wire gauge (mm)
Wire gauge (AWG)
Cable outlet
Upper temperature
Lower temperature

Female panel mount connector Push-Pull Solder 0.75 mm² 20 -85 °C

-40 °C

Electrical values

Rated voltage 125 V Rated impulse voltage 800 V Pollution degree Overvoltage category Material group Ш Rated current (40°C) 5 A Volume resistivity $\leq 3 \text{ m}\Omega$ EMV compliance shielded Degree of protection > 1000 mating cycles Mechanical operation

Material

Material of contact CuSn (Bronze)
Contact plating Au (Gold)
Material of contact body PBT (UL 94 V-0)
Material of housing CuZn (Brass nickel-plated)

Contacts: 6 DIN, female panel mount connector, screwed from front, IP 67, shielded

Product sheet

Miniature connector



Product

Pole

Contacts: 6 DIN, female panel mount connector, screwed from front, IP 67,

nielded

Sille

Area Article number Push-Pull IP67 Series 440 09 4820 81 06

