

Product	Contacts: 6, Female angled connector, overmoulded, screw type, M8x1, with hexagonal die-cast threaded ring	Area	M8 Series 718
Pole	6	Article number	77 3408 0000 50006-0500

Illustration	Scale drawing	Contact Arrangement												
		<table style="margin-left: auto; margin-right: auto;"> <tr><td>1</td><td>braun/brown</td></tr> <tr><td>2</td><td>weiß/white</td></tr> <tr><td>3</td><td>blau/blue</td></tr> <tr><td>4</td><td>schwarz/black</td></tr> <tr><td>5</td><td>grau/grey</td></tr> <tr><td>6</td><td>rosa/pink</td></tr> </table>	1	braun/brown	2	weiß/white	3	blau/blue	4	schwarz/black	5	grau/grey	6	rosa/pink
1	braun/brown													
2	weiß/white													
3	blau/blue													
4	schwarz/black													
5	grau/grey													
6	rosa/pink													

Technical data

Common values

Connector Design	Female angled connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Cable outlet	-
Upper temperature	85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	30 V
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	1.5 A
Volume resistivity	≤ 3 mΩ
EMV compliance	nicht geschirmt
Degree of protection	IP67
Mechanical operation	> 100 mating cycles

Cable data

material housing	PUR
Insulation single lead	PP
Single lead structure	32 x 0.1
Cable sheath Ø	5
Conductor resistance	60Ω/Km
Temperature range cable movable c from	-25
Temperature range cable movable c to	80
Temperature range cable fixed c from	-50
Temperature range cable fixed c to	80
Bending radius cable fixed	min. 5 x D
Bending radius cable movable	min. 10 x D
Approval	UL, CSA

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts: 6, Cable length 5 m, cable: 6 x 0.25, PUR cable sheath, female angled connector, overmoulded, screw type M8 x 1, with hexagonal die-cast threaded ring