

Product	<b>Contacts: 3, Female angled connector, overmoulded, with LED PNP NOC, VA threaded lock</b>	Area	<b>M12-A Series 763</b>
Pole	<b>3</b>	Article number	<b>77 3834 0000 50003-0500</b>

Illustration	Scale drawing	Contact Arrangement

## Technical data

### Common values

Connector Design	Female angled connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.34 mm <sup>2</sup>
Wire gauge (AWG)	22
Upper temperature	85 °C
Lower temperature	-25 °C

### Cable data

material housing	PUR
Insulation single lead	PP
Single lead structure	42 x 0.1
Cable sheath Ø	4.6
Conductor resistance	60Ω/Km (20°C)
Temperature range cable movable c from	-25
Temperature range cable movable c to	90
Temperature range cable fixed c from	-50
Temperature range cable fixed c to	80
Bending radius cable fixed	min. 10 x D
Bending radius cable movable	min. 5 x D
Approval	UL, CSA

### Electrical values

Rated voltage	36 V
Rated impulse voltage	500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	nicht geschirmt
Degree of protection	IP68
Mechanical operation	> 100 mating cycles

### Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts: 3, Cable length 5 m, cable: 3 x 0.34 mm<sup>2</sup>, PUR, female angled connector, overmoulded, with LED PNP NOC, VA threaded lock