


Product **Contacts 4: Female angled connector, crimp termination, cable outlet 6-8 mm**
 Area **M12-A Series 713**
 Article number **99 0530 52 04**


Illustration



Scale drawing



Contact Arrangement



	X	Y
1	-2,50	0,00
2	0,00	2,50
3	2,50	0,00
4	0,00	-2,50

You can find the item description and assembly instruction on the next page.

Technical data

General features

Connector locking system bolted
 Termination crimp
 Wire gauge (mm) 0,34-1,5 mm²
 Wire gauge (AWG) 22-16
 Cable outlet 6 – 8 mm
 Upper temperature 85 °C
 Lower temperature -40 °C

Electrical parameters


Rated voltage 250 V
 Rated impulse voltage 2500 V
 Pollution degree 3
 Overvoltage category II
 Material group III
 Rated current (40°C) 4 A
 Volume resistivity ≤ 3 mΩ
 EMV compliance not shielded
 Degree of protection IP67
 Mechanical operation > 50 Mating cycles

Material

Material of contact CuZn (Messing)
 Contact plating Au (gold)
 Material of contact body PA

Product **Contacts 4: Female angled connector, crimp termination, cable outlet 6-8 mm**
 Area **M12-A Series 713**
 Article number **99 0530 52 04**

Item description



Installation instructions / Mounting cutout

