

| | |
|---------------------|---|
| Product description | M12-A cable connector, Contacts: 8, not shielded, moulded on cable, IP69K, Ecolab, FDA compliant, PP grey, 8 x 0.25 mm² |
| Area | M12-A series 763 |
| Order number | 77 3729 0000 40908-0200 |

Technical data

General values

| | |
|--------------------------|----------------------|
| Connector design | cable connector |
| Connector locking system | screw |
| Termination | moulded on cable |
| Wire gauge (mm) | 0.25 mm ² |
| Wire gauge (AWG) | 24 |
| Upper limit temperature | 105 °C |
| Lower limit temperature | - 40 °C |
| Customs tariff number | 85444290 |

Cable data

| | |
|-----------------------------|---------------|
| Cable length | 2 m |
| Sheath material | PP |
| Conductor resistance | <79Ω/Km |
| Bending radius, fixed cable | ≥ 7.5 x Ø |
| Approval 1 | Ecolab |
| Approval 2 | FDA compliant |

Electrical values

| | |
|---------------------------|----------------------|
| Rated current (40 °C) | 2 A |
| Rated voltage | 30 V |
| Rated impulse voltage | 800 V |
| Pollution degree | 3 |
| Overvoltage category | II |
| Insulating material group | II |
| Insulation resistance | ≥ 10 ¹⁰ Ω |
| EMC compliance | not shielded |
| Degree of protection | IP69K |
| | IP67 |
| Degree of protection 2 | IP67 |
| Mechanical operation | > 100 Mating cycles |

Material

| | |
|-----------------------|--------------|
| Contact material | CuZn (brass) |
| Contact plating | Au (gold) |
| Contact body material | PP |
| Housing material | PP |

| | |
|---------------------|---|
| Product description | M12-A cable connector, Contacts: 8, not shielded, moulded on cable, IP69K, Ecolab, FDA compliant, PP grey, 8 x 0.25 mm² |
| Area | M12-A series 763 |
| Order number | 77 3729 0000 40908-0200 |

Security notices

The connectors are designed for use in plant, control system and electrical equipment. The end user is responsible for checking whether the connectors are suitable for use in other applications.

Connectors with degree of protection IP 67 and IP 68 are not suitable for use under water. When used outdoors, the connectors must be separately protected against corrosion. For further information about IP degrees of protection refer to 'Technical support' in the Download Centre.

To lock the cable connector to the equipment connector, the threaded ring is tightened until it is 'finger-tight' (approx. 50 cNm).